

ThermaCool® Ceiling Tile – MATERIAL SAFETY DATA

1. Chemical Product and Company Identification

Product Name	ThermaCool® Ceiling Tile. Acoustic, Textured.
Formula	n/a
Supplier	Datum Phase Change Ltd
Telephone	+44 (0) 1799 550 222
Email	info@datumphasechange.com

2. Composition Information

Patented formulation including natural mined gypsum (Calcium Sulphate Bihydrate – $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$) with reinforcing glass fibres and incorporating an organic microencapsulated phase change material.

3. Physical Data

Appearance	Perforated white colour. Textured Solid white colour.
Decomposition temperature:	$\text{CaSO}_4 + \text{H}_2\text{O}$ – about 140°C
Flammability	Limited flammability
Explosion Data	Not applicable

4. Health Hazard Data

Main Hazards:	Dust formation while drilling or sawing boards by means of electric or hand tools. Dust masks are recommended.
Other Hazards:	None

5. First Aid Measures

Specialised First Aid and Medical Treatment are required for all exposures

General Information:	The product is not classified as dangerous. In case of skin irritation, contact a dermatologist.
Eye Contact:	No specific measure required. In case of contact with dusts, wash eye with clean water. Seek medical advice if irritation persists.
Skin:	Wash off immediately with soap and water.
Inhalation:	Remove person to fresh air. Ensure supply of fresh air.

Most important symptoms and effects, both acute and delayed. – No specific symptoms or effects have been reported.

Identification of any immediate medical attention and special treatment needed. – Not applicable. Bring this document if you contact a doctor.

6. Fire Fighting Measures

Extinguishing Media:	Use extinguishing media appropriate for surrounding fire.
Special Hazards arising from the Mixture:	The product has limited fire resistance. Packaging may burn.

Advice for Fire Fighters: Hazardous combustion products may include calcium dioxide and sulphur dioxide.

7. Accidental Release Measures

Personal Precaution, protective equipment and emergency procedures – Avoid contact with eyes and skin. Use protective goggles and gloves. See sections 8 & 9.

Environmental Precautions – Keep out of drains, sewers, ditches and waterways. Minimise use of water to prevent contamination.

8. Handling and Storage

Precautions for Safe Handling: Minimise dust generation while drilling or sawing boards.

Condition for safe storage, including any

Special Conditions: Internal applications only.

9. Exposure Controls, Personal Protection Equipment

Control Parameters: Total inhalable for CaSO₄ – TWA: 5mg/m³
Exposure Controls / Personal Protection: General protective and hygiene measures: Minimise and control dust.
Respiratory protection: If dust cannot be controlled, wear a half face mask conforming to EN 140
Skin protection: Wear gloves to avoid prolonged or repeat contact
Eye protection: Wear safety goggles conforming to EN 166

10. Stability and Reactivity

Reactivity: No materials to avoid known.
Chemical Stability: Keep dry. Stable under normal storage conditions.
Conditions to Avoid: Stable if stored in dry conditions.
Hazardous Decomposition: Decomposition takes place from temperatures above 1000°C
Products:
Incompatible Materials: None known.

11. Ecological Information

Toxicity: No data available
Persistence and degradability: No data available
Bio accumulative Potential: No data available
Mobility in Soil: No data available
Results of PBT and vPvB assessment: No data available
Other Adverse Effects: Product is not allowed to discharge into aquatic environment.

12. Toxicology Information

Information on toxicological effects – No toxicological test has been completed on the product itself.

LD/LD50 Calcium Sulphate, main component: Acute oral toxicity: LD50 oral rat > 1581 mg/kg – according to guideline OECD 420
Acute inhalation toxicity: LD50 oral rat > 2.61 mg/L – according to guideline OECD 403
Skin irritation: No irritation for rabbit – according to guideline OECD 404
Sensitization: No effect anticipated. Not hazardous by OSHA criteria

13. Disposal Considerations

Waste Treatment Methods: Keep out of drains, ditches and waterways. Wastes from gypsum are normally classified as not hazardous. Do not co-dispose with municipal waste, but dispose at an authorized site in accordance with local Environmental Regulations. Non-contaminated packaging can be recycled.

14. Transport Information

Not classified as dangerous in terms of transport regulations (IMDG, ADR, RID, IACO/IATA)

NU Number: Not to apply
NU Proper Shipping Name: Not to apply
Transport Hazard Class: Not to apply
Packing Group: Not to apply
Environmental Hazard: Not to apply
Special Precaution for Users: Not to apply
Transport in Bulk According to Annex II of MARPOL 73/78 and IBC Code: Not to apply

16. Other information

As the conditions or methods of use are beyond our control, Datum Phase Change Ltd does not assume any responsibility and disclaim any liability for any use of the material. The information and data herein are believed to be accurate and have compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product in compliance with applicable state and local laws and regulations.

Datum Phase Change Ltd makes no warranty of any kind, expressed or implied, concerning the accuracy or completeness of the information and data herein. The implied warranties of merchantability and fitness for a particular purpose are specifically excluded.

The product is manufactured under a quality system certified as conforming with ISO 9001 and complies with EN 15283-2

Abbreviations and Acronyms

TWA: Time Weighted Average

LD50: Median Lethal Dose

OECD: Organisation for Economic Cooperation and Development

PBT: Persistent, Bio Accumulative, Toxic Chemical

vPvB: very Persistent, very Bio Accumulative chemical

IMDG: International Maritime Dangerous Goods

ADR: Agreement on the transport of Dangerous goods by Road

RID: Regulations on the International transport of Dangerous goods by Rail.

IATA: International Air Transport Association

Datum Phase Change Limited
Curles Manor, Pelham Road
Clavering
Essex. CB11 4PW
United Kingdom

Tel: +44 (0) 1799 550222 | Email: info@datumphasechange.com | Web: www.therma.cool